



Technical Data

# Superpanel Full Color 30

## Technical features

Dimensions	33.5 cm x 32 cm x 10 cm
Weight	3.7 kg
CRI (Colour Rendering Index)	> 95, typical 96
Dimmer 0 – 100	included
Dimming curves mode	Linear, Exponential, Logarithmic
DMX module	included
DMX (bit)	8 bit or 16 bit
Connection for 14.8 V battery with standard XLR 4 pin connector	included
Standard XLR 5 pin connectors for connection to DMX console	included
Watt consumption	200 W
Colour temperature	2700 K – 10000 K
Voltage AC	90 V – 240 V
Frecuency (input)	50/60 Hz
Compliance	CE

## Photometric data

Distance	5600 K	3200 K
Lux at 1 m	3,800	3,310
Lux at 2 m	1,020	890
Lux at 3 m	505	440
Lux at 4 m	330	290
Lux at 5 m	240	210

## Mode options

---

### **CCT (Correlated Color Temperature)**

Mode for variable color temperature control from 2700K to 10000K with the addition of plus and minus green/magenta offset.

---

### **HSI (Hue, Saturation and Intensity)**

Mode for full-color control.

---

### **RGBW**

Mode for control of Red, Green, Blue and White independently.

---

### **Preset**

Mode for a selected variety of gels.

---

### **Special Effects**

Include Strobe – Party – Copcar – Disco.

---